

Computational Science 2

[http://www.tu-chemnitz.de/physik/THUS/
lehre/CSM_SS17.php](http://www.tu-chemnitz.de/physik/THUS/lehre/CSM_SS17.php)

Seminar Exercises

Prof. M. Schreiber

Dr. P. Cain

cain@physik.tu-chemnitz.de
Room 2/P310, Phone 33144

Exercise 6 (23.05.2017):

Game of Life

from *An Introduction to Computer Simulation Methods*,
Chapter 14, Problem 14.6

- Start **LifeApp** and choose several initial configurations with a small number of live cells and determine the different types of patterns that emerge. Use the initial configurations suggested in Fig. 1 below. Does it matter whether you use fixed or periodic boundary conditions? Use a 16×16 lattice.
- Modify **LifeApp** so that each cell is initially alive with a 50% probability. Use a 32×32 lattice. What types of patterns typically result after a long time? What happens for 20% live cells? What happens for 70% live cells?
- Assume that each cell is initially alive with probability p . Given that the density of live cells at time t is $\rho(t)$, what is $\rho(t+1)$, the expected density at time $t+1$? Do the simulation and plot $\rho(t+1)$ versus $\rho(t)$. If $p = 0.5$, what is the steady-state density of live cells?
- LifeApp** has not been optimized for the Game of Life and is written so that other rules can be implemented easily. Rewrite the program so that it uses bit manipulation.



Figure 1: Examples of initial configurations